

Snorkel

S3219

ELECTRIC SLAB SCISSOR LIFTS

snorkel

S3219E



DIMENSIONS	S3219E
Max. working height	7.79m
Max. platform height (A)	5.79m
Platform size (stowed)	0.72m x 1.62m
Platform size (extended)	0.72m x 2.53m
Extension deck length	0.91m
Overall length (with step) (C)	1.78m
Overall length (without step)	1.73m
Overall width (D)	0.81m
Stowed height (B)	2.11m
Min. height (guardrails folded)	1.65m
Ground clearance (stowed)	66mm
Ground clearance (elevated)	19mm

PERFORMANCE	
Platform capacity (SWL)	250kg
Max. drive height	5.79m
Max. wind speed	12.5m/s
Max. drive speed (stowed)	3.2km/h
Max. drive speed (elevated)	0.6km/h
Raise/lower time	20/38 sec
Gradeability	25%
Inside turning radius	0.1m
Outside turning radius	1.63m
Tires	12 x 4 non-marking rubber
Controls	proportional
Drive system	2-wheel drive

POWER	
Power source	24V DC battery electric
Charger	90 - 240V, 25amp

WEIGHT	
Weight	1,438kg

TURNING RADIUS



HOISTLINE

ACCESS SPECIALISTS

WWW.HOISTLINE.COM





WWW.HOISTLINE.COM

Hire Machine or Arrange Service Job

By Visiting

www.hoistline.com

By Emailing

bookahoist@gmail.com

By Phoning

01624-618-999

Quote

Snorkel
S3219